

## OIP Server Rack 600mm Wide Specifications



<b>Weight Load Capacity</b>	Static = 1500kg Dynamic = 1000kg
<b>Frame Mountings</b>	Spaced M5 holes located in the entire frame work for mounting third party rack PDU & cable manager equipment in over 100 positions
<b>Colours</b>	RAL9004 (black) RAL7035 (grey/beige) Custom Colours upon request
<b>Frame</b>	Steel folded 9 times with a range of: 1.5mm to 4.5mm thick
<b>ANSI/EIA 310 Mounting Rails</b>	2.0mm
<b>Recessed Castor Wheel Tray</b>	2.0mm SPCC cold rolled steel for high strength torque
<b>Side Panels</b>	Toolless quick release side panels (acts a security panel as mounting is internal) 2 tier swinging side panels (for ease of installation)
<b>Other Door Options</b>	Curved Perforated Door (high air flow ventilation over 70%) Split Perforated Door
<b>Identification</b>	Mounting Rails with lasered RU identification (1-47 bottom up, millimetre numbering included) Visible on all depth braces
<b>Perforation</b>	Hexagonal Shape for high air flow ventilation
<b>Adjustable Feet</b>	Wide load bearing adjustable M10 feet Rubber base for even distributed for high weight loads